

Luceo Wall - Installation Instructions

Models LUCW-XX-RND & LUCW-XX-REC



7777 N. Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com

Please read all instructions prior to installation and keep for future reference!

1. Product to be installed by a qualified electrician.
2. Prior to installation ensure power is off at fuse box to prevent electrical shock.
3. More than one person is recommended for this installation.

1

Note: Refer to the power supply installation instruction for 24VDC wiring and additional information.

Note: More than one person is recommended for this installation.

1.1 Lay the fixture next to the wall, use a level to align & center the fixture. Then make all necessary markings to install the mounting brackets to the drywall.

2

Luceo Wall round bracket version

Luceo Wall rectangle bracket version

2.1 Carefully remove the screws from the top & bottom of the back of fixture. Then pull the mounting brackets completely out of the fixture.

3

3.1 anchor mark

round bracket version (using conduit connector)

3.1 Align and then tap each anchor onto the marks until the threaded section. Followed by tightening the anchors with a Phillips screw driver. **For round bracket version only: if using conduit connector, conduit must be present within 1.25" of the anchor to fit properly.**

4

round bracket version (no conduit connector)

rectangle bracket version

round bracket version (using conduit connector)

4.1 Line up the mounting brackets to the installed anchors, and secure using the provided screws. **If using conduit connector on the round bracket version, first secure conduit connector to mounting bracket. Then secure to the wall.**

Luceo Wall - Installation Instructions

Models LUCW-XX-RND & LUCW-XX-REC



7777 N. Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com

Please read all instructions prior to installation and keep for future reference!

1. Product to be installed by a qualified electrician.
2. Prior to installation ensure power is off at fuse box to prevent electrical shock.
3. More than one person is recommended for this installation.

Page 2 of 2

5

5.1 Feed fixture power wires to the power supply.

5.2 Align the fixture to the mounting brackets & secure by using the fixture screws.

5.3 For round bracket version only: if using the conduit connector to drywall, you may have to use mud, sand & paint to complete.

6

6.1 Connect +24 VDC red wire from the fixture to the power supply +24 VDC red wire with a wire nut. Connect -24VDC black wire from the fixture to power supply -24VDC black wire with a wire nut.