



LETO 44

SURFACE MOUNT CYLINDER
TUNABLE WHITE & WARM DIM



Features

- Faceted and Smooth reflectors provide beam spreads between 15° to 60°.
- Four output options available up to 2000 lumens.
- Nine driver selections available to cover wide range of applications.
- Five year warranty.



Finish Options

- White
- Black
- Silver
- Mocha
- Charcoal
- Cerulean
- Firebrick



Technical Information

TYPE	WD1830				TW2765
	700 lm	1000lm	1500lm	2000lm	1500lm
OUTPUT OPTIONS	700 lm	1000lm	1500lm	2000lm	1500lm
Fixture wattage	7.2 W	11.4 W	16.3 W	21.6 W	22.6 W
Delivered Lumen	719 lm	1154 lm	1628 lm	2063 lm	1786 lm
Efficacy	100 lm/W	101 lm/W	100 lm/W	96 lm/W	79 lm/W
Center Beam Candlepower (15° Faceted Reflector)	3277 cd	5260 cd	7421 cd	9404 cd	7432 cd

CCT	CRI	TM-30		
		R _f	R _g	R ₉
1800K	94	90	93	61
3000K	94	89	97	72
2700K	91	90	96	59
6500K	93	87	97	73

Ordering Code

Integral Driver Example: Fixture LET44-SM-S-07-WD1830-F15-NA-WH-WH-PHSD-NA

Remote Driver Example: Fixture LET44-SM-S-07-WD1830-F15-NA-WH-WH-PHSD-NA-HRM-LET44-SM-07-WD1830-PHSD-NA

Fixture

MODEL	TYPE	SIZE	OUTPUT	CCT	OPTIC	ACCESSORY	BODY FINISH	BAFFLE FINISH
LET44-Leto 44	SM-Surface Mount	S-Small ^{1,2} M-Medium L-Large	07-700 10-1000 15-1500 ³ 20-2000	WD1830-Warm Dim, TW2765-1800K-3000K Tunable White, 2700K-6500K ^{2,3,9,10}	F15-15 Degree, Faceted F30-30 Degree, Faceted F45-45 Degree, Faceted F60-60 Degree, Faceted S30-30 Degree, Smooth S45-45 Degree, Smooth	NA-No Accessory CL-Clear Lens DL-Diffusing Lens HC-Honeycomb Louver SL-Solite Lens	Standard WH-White BK-Black SL-Silver Premium ⁴ MA-Mocha CC-Charcoal CR-Cerulean FB-Firebrick	Standard WH-White BK-Black SL-Silver Premium ⁴ MA-Mocha CC-Charcoal CR-Cerulean FB-Firebrick
				DRIVER	DRIVER OPTIONS⁸			

PHSD - Forward/Reverse Phase, 1% Dimming, 120V Only
 010S - 0-10V, 1% Dimming, 120/277V
 0103 - 0-10V, 1% Dimming, 347V Only⁶
 010L - EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V⁶
 010G - EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V⁶
 DALI - EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V⁶
 DALI8 - EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V⁶
 LUTE - Lutron Hilume Ecodigital, 1% Dimming, 120V/277V^{5,6}
 DMX - EldoLED, DMX, 0.1% Dimming, 120V/277V⁶

NA - None
 EMG - Emergency Driver^{6,7}

1 - Size Small max output is 1000 lumens.
 2 - Size Small is not available with TW2765.
 3 - TW2765 only available with 1500 lumens.
 4 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
 5 - LUTE driver is not available at 700 lumens.
 6 - Drivers: 0103/010L/010G/DALI/DALI8/DMX/LUTE/EMG always require a remote driver.

7 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 0103, DMX, DALI8 or LUTE Driver.
 8 - AWRN/CSMB available upon request, contact Senso for details.
 9 - TW2765 only available with Drivers 010L/010G/DALI8/DMX. Not available with EMG driver option.
 10 - TW2765 requires HRM - Remote Power Supply.

CONTACT FACTORY FOR MORE OPTIONS.

LETO 44

SURFACE MOUNT CYLINDER
TUNABLE WHITE & WARM DIM

Lens

CL
Clear Lens



DL
Diffusing Lens



HC
Honeycomb



SL
Solite Lens



Optics

FXF (15°, 30°, 45°, 60°)
Faceted Reflector



SXX (30°, 45°)
Smooth Reflector



LETO 44

SURFACE MOUNT CYLINDER
TUNABLE WHITE & WARM DIM

Remote Driver Housing


Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.

REMOTE DRIVER	MODEL	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM-Housing, Remote	LET44-SM-Leto 44 Surface Mount	Same as Fixture	Same as Fixture	Same as Fixture	Same as Fixture

Maximum mounting distance to luminaire using 18 AWG wire								
PHSD	010S	0103	010L	010G	DALI	DALI8	LUTE	DMX
16'	16'	16'	72'	72'	72'	72'	15'	149'


4" J-box

Minimum volume required to mount drivers in junction box: 70mm x 40mm x 30mm.




Driver
PHSD
010S

HRM Single with Externally Mounted Driver



Driver
0103
010L
010G
DALI
LUTE


HRM Double



Driver
DALI8
DMX

EMG Emergency Driver

120 minute EMG operation time.



Driver
EMG

LETO 44


SURFACE MOUNT CYLINDER
TUNABLE WHITE & WARM DIM

Standard Finish

BK
Black



WH
White



SL
Silver



Premium Finish

Two tone with Black Baffle Finish. Any combination may be used for baffle and body finishes.


MA
Mocha




CC
Charcoal



CR
Cerulean




FB
Firebrick



TM-30


Warm Dim 1800K

COLOR VECTOR GRAPHIC




Warm Dim 3000K

COLOR VECTOR GRAPHIC




Tunable White 2700K

COLOR VECTOR GRAPHIC





Tunable White 6500K

COLOR VECTOR GRAPHIC





Photometry



15° Faceted Reflector





30° Smooth Reflector





30° Faceted Reflector



45° Smooth Reflector



45° Faceted Reflector



60° Faceted Reflector

