BXC Basics X-Large Channel

Contractor Grade Extruded aluminum profile





Features

Basics Contractor-Grade x-large extrusions compatible with Basics LED strips.

Finish

Silver anodized Channel

Diffuser Lens

Polycarbonate, snap-in-place, UV resistant


Mounting


Multiple mounting clip


Warranty


5 Years

Product Dimensions









INCLUDED MOUNTING ACCESSORIES		
EXTRUSION LENGTH	MOUNTING HARDWARE	END CAP (PAIR)
84"	6	1


Each pair of endcaps includes 1x HO (no wire feed hole) and 1x HI (with hole) where applicable. Additional endcaps and mounting clips are available for purchase

TRANSMISSION PERCENTAGE (COMPARED TO LED TAPE WITHOUT CHANNEL)

LENS	TRANSMISSION %
Frosted	47%

See LED tape spec sheet for lens dotting characteristics & compatibility

Ordering code







Accessories

All Channels come with a specified set of Mounting Clips and End Caps, see Ordering Code for details. Order additional Mounting Clips and End Caps as necessary.

EC-BXC-H0-SASilver Anodized End Cap



EC-BXC-H1-SASilver Anodized End Cap with powerfeed opening



MB-BXC-SS Fixed Clip -FC

