

LATONA 2" WET

DOWNLIGHT






Features

- Faceted metal reflectors provide beam spreads between 20° to 60°.
- Three output options available up to 1500 lumens.
- Nine drivers selections available to cover wide range of applications.
- Five year warranty.

Finish Options

- ☐ White
- ☐ Black
- ☐ Silver



Technical Information

OUTPUT OPTIONS	700 lm	1000lm	1500lm
Fixture wattage	6.3 W	9.8 W	14.7 W
Delivered Lumen at 3500K	625 lm	904 lm	1394 lm
Efficacy	99 lm/W	92 lm/W	95 lm/W
Center Beam Candlepower (20° Faceted Reflector)	1521 cd	2200 cd	3393 cd

CCT	Multiplier	CRI	TM-30		
			R _f	R _g	R ₉
2500K	0.80	93+	93	102	50+
2700K	0.92	93+	92	100	50+
3000K	0.97	93+	92	103	50+
3500K	1.00	93+	93	102	50+
4000K	1.07	93+	92	101	50+
6500K	1.05	93+	92	101	50+

Ordering Code

Remote Driver Example: Fixture LAT2W-D-RD-TR-07-25K-F20-NA-WHHRM-LAT2-D-TR-07-25K-PHSD-NA

Fixture

MODEL	TYPE	SHAPE	TRIM	OUTPUT	CCT	OPTIC	ACCESSORY	TRIM FINISH
LAT2W - Latona 2" Wet	D - Downlight	RD - Round SQ - Square	TR - Trimmed	07 - 700 lumens (6.3W) 10 - 1000 lumens (9.8W) 15 - 1500 lumens (14.7W)	25K - 2500K 27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K 65K - 6500K	F20 - 20 Degree, Faceted F30 - 30 Degree, Faceted F60 - 60 Degree, Faceted	CL - Clear Lens DL - Diffusing Lens	Standard WH - White BK - Black SL - Silver

HOUSING	MODEL	TRIM	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM - Remote Power Supply (Non-IC) HP - New Construction Pan (Non-IC) HIC - Housing, IC Rated ¹	LAT2-D - Latona 2" Downlight	Same as Fixture	Same as Fixture	Same as Fixture	PHSD - Forward/Reverse Phase, 1% Dimming, 120V Only 010S - 0-10V, 1% Dimming, 120/277V 0103 - 0-10V, 1% Dimming, 347V Only ³ 010L - EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V ³ 010G - EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V ³ DALI - EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V ³ DALI8 - EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V ³ LUTE - Lutron HiLume Ecodigital, 1% Dimming, 120V/277V ^{2,3} DMX - EldoLED, DMX, 0.1% Dimming, 120V/277V ³	NA - None EMG - Emergency Driver ^{3,4}

1 - Housing HIC is only available with 700/1000 lumens

2 - LUTE driver is not available with 700 lumens.

3 - Drivers 0103/010L/010G/DALI/DALI8/LUTE/DMX/EMG are only available with HRM - Remote Power Supply.

4 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 0103, DMX, DALI8 or LUTE Driver.

CONTACT FACTORY FOR MORE OPTIONS.

Round

TR
Trimmed



Lens

CL
Clear Lens



DL
Diffusing Lens



Optics

FXX (20°, 30°, 60°)
Faceted Reflector




Square

TR
Trimmed



Lens

CL
Clear Lens




DL
Diffusing Lens



Optics

FXX (20°, 30°, 60°)
Faceted Reflector




Remote Driver Housing

Maximum mounting distance to luminaire using 18 AWG wire


PHSD	010S	0103	010L	010G	DALI	DALI8	LUTE	DMX
16'	16'	16'	72'	72'	72'	72'	15'	149'

HRM Single with Externally Mounted Driver




Driver	+	Driver Option
010L	+	NA
010G	+	NA
010S	+	NA
DALI	+	NA
LUTE	+	NA

HRM Single




Driver	+	Driver Option
PHSD	+	NA

HRM Double



Driver	+	Driver Option
DALI8	+	NA
DMX	+	NA

EMG Emergency Driver (120 minutes EMG operation time)






Driver	+	Driver Option
010L	+	EMG
010G	+	EMG
010S	+	EMG
DALI	+	EMG
PHSD	+	EMG



Remote Driver Housing

HP

New Construction Pan (Non-IC)






Driver	+	Driver Option
PHSD	+	NA
O10S	+	NA



HIC/HCP

Housing, IC Rated/ Housing, IC Rated, Chicago Plenum Rated



Driver	+	Driver Option
PHSD	+	NA
O10S	+	NA

LATONA 2" WET

DOWNLIGHT



Standard Finish


BK
Black



WH
White




SL
Silver




TM-30


2500K




2700K




3000K




3500K



4000K





6500K





Photometry

Tested with Clear Lens.

20° Faceted Reflector



30° Faceted Reflector



60° Faceted Reflector

