

Power Supplies have been changed in name only, there have been no changes made to their functionality. This was done with the intention of improving consistency across Luminii and our brands as well as making it easier to identify and differentiate between different power supplies, helping our customers experience.

OLD Model	NEW Model	NEW Model Description
PDCU-D-30-24	PS-UNI-D-30-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming (1%), Dry- 30 Watts- 24 VDC
PDCU-D-60-24	PS-UNI-D-60-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Dry- 60 Watts- 24 VDC
PDCU-D-96-24	PS-UNI-D-96-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Dry- 96 Watts- 24 VDC
PDCU-D-3x96-24	PS-UNI-D-3X96-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Dry- 3x96 Watts- 24 VDC
PDCU-W-30-24	PS-UNI-W-30-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Wet- 30 Watts- 24 VDC
PDCU-W-60-24	PS-UNI-W-60-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Wet- 60 Watts- 24 VDC
PDCU-W-96-24	PS-UNI-W-96-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Wet- 96 Watts- 24 VDC
PDCU-W-3x96-24	PS-UNI-W-3X96-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Wet- 3x96 Watts- 24 VDC
PDCU-PR-96-24	PS-UNI-PR-96-24	Power Supply, 120-277VAC- 0-10V, Phase Dimming, Pool Rated- 96 Watts- 24 VDC
PDC-96-24	PS-PH-D-96-24-DC	Power Supply, 120-277VAC- Phase Dimming (Triac, ELV, MLV)- Dry- 96 Watts- 24 VDC- Direct Current
PSDALI-96-24	PS-DALI-D-96-24	Power Supply, 120-277VAC- DALI (0.1%)- Dry- 96 Watts- 24 VDC
PSDALI-DT8-96-24	PS-DALI-DT8-D-96-24	Power Supply, 120-277VAC- DALI DT8 Tunable White (0.1%)- Dry- 96 Watts- 24 VDC
PSDALI-DT8-96-24-AWNR	PS-DALI-DT8-D-96-24-AWNR	Power Supply, 120-277VAC- DALI DT8 Tunable White (0.1%)- Dry- 96 Watts- 24 VDC- Athena
PSDALI-3X96-24	PS-DALI-D-3X96-24	Power Supply, 120-277VAC- DALI (0.1%)- Dry- 3x96 Watts- 24 VDC
PSDMX-96-24	PS-DMX-D-96-24	Power Supply, 120-277VAC- DMX (0.1%)- Dry- 96 Watts- 24 VDC
PSDMX-3X96-24	PS-DMX-D-3X96-24	Power Supply, 120-277VAC- DMX (0.1%)- Dry- 3x96 Watts- 24 VDC
PS010V-96-24-LIN	PS-010V-LIN-D-96-24	Power Supply, 120-277VAC- 0-10V Dimming (0.1%), Linear- Dry- 96 Watts- 24 VDC
PS010V-96-24-LIN-AWNR	PS-010V-LIN-D-96-24-AWNR	Power Supply, 120-277VAC- 0-10V Dimming (0.1%), Linear- Dry- 96 Watts- 24 VDC- Athena
PS010V-96-24-LOG	PS-010V-LOG-D-96-24	Power Supply, 120-277VAC- 0-10V Dimming (0.1%), Logarithmic- Dry- 96 Watts- 24 VDC
PS010V-96-24-LOG-AWNR	PS-010V-LOG-D-96-24-AWNR	Power Supply, 120-277VAC- 0-10V Dimming (0.1%), Logarithmic- Dry- 96 Watts- 24 VDC- Athena
PS010V-3X96-24-LIN	PS-010V-LIN-D-3X96-24	Power Supply, 120-277VAC- 0-10V Dimming (0.1%), Linear- Dry- 3x96 Watts- 24 VDC
PS010V-3X96-24-LOG	PS-010V-LOG-D-3X96-24	Power Supply, 120-277VAC- 0-10V Dimming (0.1%), Logarithmic- Dry- 3x96 Watts- 24 VDC
PS010VD-96-24-WW	PS-010V-WD-D-96-24	Power Supply, 120-277VAC- 0-10V Dimming, Standard Warm Dim Curve (with Dynamic White LED)- Dry- 96 Watts- 24 VDC
PS010VD-96-24-WW-AWNR	PS-010V-WD-D-96-24-AWNR	Power Supply, 120-277VAC- 0-10V Dimming, Standard Warm Dim Curve (with Dynamic White LED)- Dry- 96 Watts- 24 VDC- Athena
PS010VD-96-24-W2C	PS-010V-TW-D-96-24	Power Supply, 120-277VAC- 0-10V Dimming, Two Channel Control, Brightness and CCT1-CCT2 Ratio- Dry- 96 Watts- 24 VDC
PS010VD-96-24-W2I	PS-010V-2CH-D-96-24	Power Supply, 120-277VAC- 0-10V Dimming, Two Channel Control, LED1 Brightness and LED2 Brightness- Dry- 96 Watts- 24 VDC
PS010VD-96-24-W2I-AWNR	PS-010V-2CH-D-96-24-AWNR	Power Supply, 120-277VAC- 0-10V Dimming, Two Channel Control, LED1 Brightness and LED2 Brightness- Dry- 96 Watts- 24 VDC- Athena
PS010VD-96-24-W1X	PS-010V-WDX-D-96-24	Power Supply, 120-277VAC- 0-10V Dimming, Customizable Warm Dim Curve (with Dynamic White LED)- Dry- 96 Watts- 24 VDC
PS010VD-96-24-W2X	PS-010V-2CHX-D-96-24	Power Supply, 120-277VAC- 0-10V Dimming, Two Channel Control, Customizable Brightness and CCT1-CCT2 Ratio- Dry- 96 Watts- 24 VDC
PS010VD-3x96-24-WW	PS-010V-WD-D-3X96-24	Power Supply, 120-277VAC- 0-10V Dimming, Standard Warm Dim Curve (with Dynamic White LED)- Dry- 3x96 Watts- 24 VDC
PS010VD-3x96-24-W2C	PS-010V-TW-D-3X96-24	Power Supply, 120-277VAC- 0-10V Dimming, Two Channel Control, Brightness and CCT1-CCT2 Ratio- Dry- 3x96 Watts- 24 VDC
PSV-96-24-ND-D	PS-ND-D-96-24	Power Supply, 120-277VAC- Non Dimming, Dry- 96 Watts- 24 VDC
PSV-96-24-ENL-D	PS-010V-D-96-24-ENL	Power Supply, 120-277VAC- 0-10V Dimming (1%)- Dry- 96 Watts- 24 VDC- 0-10V Enlightened
IG-CVE-96X2D-24	PS120-ELV-IG-2X96-24	Power Supply, 120VAC- ELV Dimming, In Ground- 2x96 Watts- 24 VDC
IG-CVE-96X2D-24-240	PS240-ELV-IG-2X96-24	Power Supply, 240VAC- ELV Dimming, In Ground- 2x96 Watts- 24 VDC
IG-CVE-96X2D-24-277	PS277-ELV-IG-2X96-24	Power Supply, 277VAC- ELV Dimming, In Ground- 2x96 Watts- 24 VDC