


# SOLO 16 STUCCHI

## 6° ULTRA NARROW BEAM



### TECHNICAL DESCRIPTION

Solo 16 Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The ultra narrow beam in our 8.40W 700lm module has a peak intensity of 28223cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

### MECHANICAL & ELECTRICAL

<b>CATEGORY</b> IP20	<b>WATTAGE</b> 8.40W
<b>MATERIAL</b> Machined AL 6063-T6   Machined Brass	<b>FORWARD VOLTAGE</b> 48V
<b>PAN</b> 360°	<b>SUPPLY TYPE</b> Constant Voltage
<b>TILT</b> 90°	<b>DRIVER LOCATION</b> Remote AC to 48VDC
<b>LOCKABLE</b> Pan	<b>DIMMING</b> DALI   0-10V   1-10V   Casambi
<b>WEIGHT</b> 395g 570g*   0.87lb 1.25lb*	

### MOUNTING




**MOUNTING** 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

### FINISHES


**FINISHES** Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze\* | Polished Brass\* | Satin Brass\*

\*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

### OPTICAL & STANDARDS

<b>NOMINAL LUMENS</b> 700lm	<b>BEAM ANGLE</b> 6°
<b>DELIVERED LUMENS</b> 650lm	<b>CRI</b> 92 TYP
<b>COLOUR TEMPERATURE</b> 2700K   3000K	<b>TM-30</b> RF: 90 RG: 99
<b>ACCESSORY HOLDER</b> Separate	<b>WARRANTY</b> 5 Years
<b>ACCESSORIES</b> Lenses   Louver 55mm (2.16")	<b>LIFETIME</b> L90B10 100,000hrs
<b>TM65</b> 17.37kgCO2e	<b>STANDARDS</b>
<b>TM66</b> 2.4	   

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> </ul>	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> <li>A Brushed Aluminium</li> <li>R Rubbed Bronze*</li> <li>P Polished Brass*</li> <li>S Brushed Brass*</li> </ul>	<ul style="list-style-type: none"> <li>2792 2700K 92CRI</li> <li>3092 3000K 92CRI</li> <li>4092 4000K 92CRI</li> </ul>	<ul style="list-style-type: none"> <li>06 Ultra Narrow</li> <li>10 Narrow</li> <li>15 Medium</li> <li>30 Flood</li> <li>55 Wide Flood</li> </ul>	<ul style="list-style-type: none"> <li>A 0-10V</li> <li>B 1-10V</li> <li>C Casambi</li> <li>D DALI</li> </ul>

Example Code: 1052 - TT - 309210 - D

\*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

# SOLO 16 STUCCHI

10° NARROW BEAM



## TECHNICAL DESCRIPTION

Solo 16 Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The narrow beam in our 8.40W 700lm module has a peak intensity of 15476cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

## MECHANICAL & ELECTRICAL

<b>CATEGORY</b> IP20	<b>WATTAGE</b> 8.40W
<b>MATERIAL</b> Machined AL 6063-T6   Machined Brass	<b>FORWARD VOLTAGE</b> 48V
<b>PAN</b> 360°	<b>SUPPLY TYPE</b> Constant Voltage
<b>TILT</b> 90°	<b>DRIVER LOCATION</b> Remote AC to 48VDC
<b>LOCKABLE</b> Pan	<b>DIMMING</b> DALI   0-10V   1-10V   Casambi
<b>WEIGHT</b> 395g 570g*   0.87lb 1.25lb*	

## MOUNTING





**MOUNTING** 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

## FINISHES


**FINISHES** Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze\* | Polished Brass\* | Satin Brass\*

\*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

## OPTICAL & STANDARDS

<b>NOMINAL LUMENS</b> 700lm	<b>BEAM ANGLE</b> 10°
<b>DELIVERED LUMENS</b> 653lm	<b>CRI</b> 92 TYP
<b>COLOUR TEMPERATURE</b> 2700K   3000K	<b>TM-30</b> RF: 90 RG: 99
<b>ACCESSORY HOLDER</b> Separate	<b>WARRANTY</b> 5 Years
<b>ACCESSORIES</b> Lenses   Louver 55mm (2.16")	<b>LIFETIME</b> L90B10 100,000hrs
<b>TM65</b> 17.37kgCO2e	<b>STANDARDS</b>
<b>TM66</b> 2.4	   

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> </ul>	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> <li>A Brushed Aluminium</li> <li>R Rubbed Bronze*</li> <li>P Polished Brass*</li> <li>S Brushed Brass*</li> </ul>	<ul style="list-style-type: none"> <li>2792 2700K 92CRI</li> <li>3092 3000K 92CRI</li> <li>4092 4000K 92CRI</li> </ul>	<ul style="list-style-type: none"> <li>06 Ultra Narrow</li> <li>10 Narrow</li> <li>15 Medium</li> <li>30 Flood</li> <li>55 Wide Flood</li> </ul>	<ul style="list-style-type: none"> <li>A 0-10V</li> <li>B 1-10V</li> <li>C Casambi</li> <li>D DALI</li> </ul>

Example Code: 1052 - TT - 309210 - D

\*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

# SOLO 16 STUCCHI

## 16° MEDIUM BEAM



### TECHNICAL DESCRIPTION

Solo 16 Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The medium beam in our 8.40W 700lm module has a peak intensity of 5671cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

### MECHANICAL & ELECTRICAL

<b>CATEGORY</b> IP20	<b>WATTAGE</b> 8.40W
<b>MATERIAL</b> Machined AL 6063-T6   Machined Brass	<b>FORWARD VOLTAGE</b> 48V
<b>PAN</b> 360°	<b>SUPPLY TYPE</b> Constant Voltage
<b>TILT</b> 90°	<b>DRIVER LOCATION</b> Remote AC to 48VDC
<b>LOCKABLE</b> Pan	<b>DIMMING</b> DALI   0-10V   1-10V   Casambi
<b>WEIGHT</b> 395g 570g*   0.87lb 1.25lb*	

### MOUNTING





**MOUNTING** 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

### FINISHES


**FINISHES** Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze\* | Polished Brass\* | Satin Brass\*

\*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

### OPTICAL & STANDARDS

<b>NOMINAL LUMENS</b> 700lm	<b>BEAM ANGLE</b> 16°
<b>DELIVERED LUMENS</b> 623lm	<b>CRI</b> 92 TYP
<b>COLOUR TEMPERATURE</b> 2700K   3000K	<b>TM-30</b> RF: 90 RG: 99
<b>ACCESSORY HOLDER</b> Separate	<b>WARRANTY</b> 5 Years
<b>ACCESSORIES</b> Lenses   Louver 55mm (2.16")	<b>LIFETIME</b> L90B10 100,000hrs
<b>TM65</b> 17.37kgCO2e	<b>STANDARDS</b>
<b>TM66</b> 2.4	   

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> </ul>	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> <li>A Brushed Aluminium</li> <li>R Rubbed Bronze*</li> <li>P Polished Brass*</li> <li>S Brushed Brass*</li> </ul>	<ul style="list-style-type: none"> <li>2792 2700K 92CRI</li> <li>3092 3000K 92CRI</li> <li>4092 4000K 92CRI</li> </ul>	<ul style="list-style-type: none"> <li>06 Ultra Narrow</li> <li>10 Narrow</li> <li>15 Medium</li> <li>30 Flood</li> <li>55 Wide Flood</li> </ul>	<ul style="list-style-type: none"> <li>A 0-10V</li> <li>B 1-10V</li> <li>C Casambi</li> <li>D DALI</li> </ul>

Example Code: 1052 - TT - 309210 - D

\*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

# SOLO 16 STUCCHI

## 30° FLOOD BEAM



### TECHNICAL DESCRIPTION

Solo 16 Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The flood beam in our 8.40W 700lm module has a peak intensity of 1652cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

### MECHANICAL & ELECTRICAL

<b>CATEGORY</b> IP20	<b>WATTAGE</b> 8.40W
<b>MATERIAL</b> Machined AL 6063-T6   Machined Brass	<b>FORWARD VOLTAGE</b> 48V
<b>PAN</b> 360°	<b>SUPPLY TYPE</b> Constant Voltage
<b>TILT</b> 90°	<b>DRIVER LOCATION</b> Remote AC to 48VDC
<b>LOCKABLE</b> Pan	<b>DIMMING</b> DALI   0-10V   1-10V   Casambi
<b>WEIGHT</b> 395g 570g*   0.87lb 1.25lb*	

### MOUNTING





**MOUNTING** 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

### FINISHES


**FINISHES** Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze\* | Polished Brass\* | Satin Brass\*

\*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

### OPTICAL & STANDARDS

<b>NOMINAL LUMENS</b> 700lm	<b>BEAM ANGLE</b> 30°
<b>DELIVERED LUMENS</b> 637lm	<b>CRI</b> 92 TYP
<b>COLOUR TEMPERATURE</b> 2700K   3000K	<b>TM-30</b> RF: 90 RG: 99
<b>ACCESSORY HOLDER</b> Separate	<b>WARRANTY</b> 5 Years
<b>ACCESSORIES</b> Lenses   Louver 55mm (2.16")	<b>LIFETIME</b> L90B10 100,000hrs
<b>TM65</b> 17.37kgCO2e	<b>STANDARDS</b>
<b>TM66</b> 2.4	   

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> </ul>	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> <li>A Brushed Aluminium</li> <li>R Rubbed Bronze*</li> <li>P Polished Brass*</li> <li>S Brushed Brass*</li> </ul>	<ul style="list-style-type: none"> <li>2792 2700K 92CRI</li> <li>3092 3000K 92CRI</li> <li>4092 4000K 92CRI</li> </ul>	<ul style="list-style-type: none"> <li>06 Ultra Narrow</li> <li>10 Narrow</li> <li>15 Medium</li> <li>30 Flood</li> <li>55 Wide Flood</li> </ul>	<ul style="list-style-type: none"> <li>A 0-10V</li> <li>B 1-10V</li> <li>C Casambi</li> <li>D DALI</li> </ul>

Example Code: 1052 - TT - 309210 - D

\*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

# SOLO 16 STUCCHI

## 50° WIDE FLOOD BEAM



### TECHNICAL DESCRIPTION

Solo 16 Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The wide flood beam in our 8.40W 700lm module has a peak intensity of 633cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

### MECHANICAL & ELECTRICAL

<b>CATEGORY</b> IP20	<b>WATTAGE</b> 8.40W
<b>MATERIAL</b> Machined AL 6063-T6   Machined Brass	<b>FORWARD VOLTAGE</b> 48V
<b>PAN</b> 360°	<b>SUPPLY TYPE</b> Constant Voltage
<b>TILT</b> 90°	<b>DRIVER LOCATION</b> Remote AC to 48VDC
<b>LOCKABLE</b> Pan	<b>DIMMING</b> DALI   0-10V   1-10V   Casambi
<b>WEIGHT</b> 395g 570g*   0.87lb 1.25lb*	

### MOUNTING





**MOUNTING** 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

### FINISHES


**FINISHES** Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze\* | Polished Brass\* | Satin Brass\*

\*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

### OPTICAL & STANDARDS

<b>NOMINAL LUMENS</b> 700lm	<b>BEAM ANGLE</b> 50°
<b>DELIVERED LUMENS</b> 605lm	<b>CRI</b> 92 TYP
<b>COLOUR TEMPERATURE</b> 2700K   3000K	<b>TM-30</b> RF: 90 RG: 99
<b>ACCESSORY HOLDER</b> Separate	<b>WARRANTY</b> 5 Years
<b>ACCESSORIES</b> Lenses   Louver 55mm (2.16")	<b>LIFETIME</b> L90B10 100,000hrs
<b>TM65</b> 17.37kgCO2e	<b>STANDARDS</b>
<b>TM66</b> 2.4	   

Photometry shown is for 3000K module. Please enquire for other CCT photometry.



MODEL	TRACK & ADAPTER FINISH	LUMINAIRE FINISH	LED CCT	BEAM ANGLE	DIMMING CONTROL
1052	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> </ul>	<ul style="list-style-type: none"> <li>T White 9016</li> <li>B Black 9005</li> <li>A Brushed Aluminium</li> <li>R Rubbed Bronze*</li> <li>P Polished Brass*</li> <li>S Brushed Brass*</li> </ul>	<ul style="list-style-type: none"> <li>2792 2700K 92CRI</li> <li>3092 3000K 92CRI</li> <li>4092 4000K 92CRI</li> </ul>	<ul style="list-style-type: none"> <li>06 Ultra Narrow</li> <li>10 Narrow</li> <li>15 Medium</li> <li>30 Flood</li> <li>55 Wide Flood</li> </ul>	<ul style="list-style-type: none"> <li>A 0-10V</li> <li>B 1-10V</li> <li>C Casambi</li> <li>D DALI</li> </ul>


Example Code: 1052 - TT - 309210 - D

\*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

DRIVER COMPATIBILITY

MEANWELL | 60W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 6  
 MIN DIM LEVEL N/A Dimming direct to track  
 VOLTAGE REGION 230V  
 FOR NORTH AMERICA No  
 WATTAGE 60W  
 OUTPUT VOLTAGE 48V  
 SUPPLY TYPE Constant Voltage  
 DRIVER LOCATION Remote  
 MANUFACTURER Meanwell




ORDER CODE PSCV-60-48-N1-MW

LENGTH 162mm (6.38") WIDTH 42mm (1.65") HEIGHT 32mm (1.23")



MEANWELL | 100W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 10  
 MIN DIM LEVEL N/A Dimming direct to track  
 VOLTAGE REGION 230V  
 FOR NORTH AMERICA No  
 WATTAGE 100W  
 OUTPUT VOLTAGE 48V  
 SUPPLY TYPE Constant Voltage  
 DRIVER LOCATION Remote  
 MANUFACTURER Meanwell




ORDER CODE PSCV-100-48-N1-MW

LENGTH 190mm (7.48") WIDTH 52mm (2.04") HEIGHT 37mm (1.46")



MEANWELL | 100W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 10  
 MIN DIM LEVEL N/A Dimming direct to track  
 VOLTAGE REGION 120V  
 FOR NORTH AMERICA Yes  
 WATTAGE 100W  
 OUTPUT VOLTAGE 48V  
 SUPPLY TYPE Constant Voltage  
 DRIVER LOCATION Remote  
 MANUFACTURER Meanwell



ORDER CODE USCV-100-48-N1-MW-EN

LENGTH 350mm (13.75") WIDTH 65mm (2.6") HEIGHT 57mm (2.25")




# SOLO 16 SERIES SPOTLIGHT ACCESSORIES

FOR USE WITH SOLO 16 INTENSE | PLUS | DYNAMIC WHITE

## ACCESSORIES

The Solo 16 series track and surface spotlights can accommodate accessories with a snap in accessory holder.



### Double Accessory Holder

*Can hold 2 accessories*

**HEIGHT**      14mm ( 0.551" )  
**DAIMETER**      63mm ( 2.480" )




**PART CODE**      254-BK

### Honeycomb Louvre

*Enhances glare control*

**THICKNESS**      3.2mm ( 0.126" )  
**DAIMETER**      55mm ( 2.165" )



**PART CODE**      995-55-BK

### 1/4 CTO Dichroic

*CCT warming - approx 300K*

**THICKNESS**      1.8mm ( 0.071" )  
**DAIMETER**      55mm ( 2.165" )




**PART CODE**      997-1/4CTO-55

### Softening Lens

*Heavy Diffusion of beam*

**THICKNESS**      3.2mm ( 0.126" )  
**DAIMETER**      55mm ( 2.165" )



**PART CODE**      991-55

### Linear Lens

*Elongates beam*

**THICKNESS**      3.9mm ( 0.154" )  
**DAIMETER**      55mm ( 2.165" )



**PART CODE**      992-55