



\* MFG Model Number: BA42WETXX



## Features

BA140-IP65 series is a Contractor Grade, efficient, field configurable and durable waterproof LED strip suitable for wet installations.

### Mounting

BA strip is equipped with 3M™ adhesive transfer tape.

### Applications

Indoor and wet locations - millwork, cove, architectural reveals, undercabinet, display case, handrail, accent lighting.

### Approvals

CE, UKCA, UL, Class 2, IP65

### Operating voltage

24 VDC

### Average Life (L70)

50,000 hours


### Warranty

5 years



## Technical information

TYPE	BA140-IP65		
OUTPUT OPTIONS	SO	HO	VHO
Lumens Output (3000K)	476 lm/m	997 lm/m	1463 lm/m
Average Power Consumption	6.6 W/m	13 W/m	19.7 W/m
Efficacy	73 lm/W	76 lm/W	74 lm/W
Ordering Increment (mm)	50 mm		
LED/Meter	140		
Max Run Length (in series to 96W)	15 m	8 m	5 m
Dimensions	12 mm W x 6 mm H		
Ambient Operating Temperature Range	-40° C - 40° C		



CCT	Multiplier (reference - 3000K)	CRI
2700K	0.91	90
3000K	1.00	90
4000K	1.09	90

## Ordering code

MODEL	OUTPUT	CCT	REEL SIZE
BA140-IP65 - Basics Strip, Wet Location	SO - Standard HO - High VHO - Very High	27K - 2700K 30K - 3000K 40K - 4000K	R10m - Reel, 10 meter




## Minii Connectors

Minii connectors are easy, field-installable accessories that make joining BA140-IP65 strip simple! Their minimal width allows them to fit into extrusions, while their transparent frame eliminates dark spots.


### BA-IP65-PJC-10

Wet jumper minii connector with 76mm wire for BA140-IP65 LED strip




### BA-IP65-PFC-10-1M

Wet Power feed minii connector with 1m wire for BA140-IP65 Wet LED strip




## Sample Layout



## Accessories


### LVSP-IP66

Splice box: wet rated, low voltage, gray, IP66



### CL2


Mounting clip



Recommended every 300mm when LineLED strip is facing down


### LL-ZIP

Cable/Wire Strain Relief Clip




### LVSP-IP66-CM

Connector for splice box, low voltage for cable management, gray, IP66



### EC-SIL-10MM

Silicone End Cap for sealing the end of BA140-IP65 Wet LED strip



### SIL-502-RTV


ASI 502 high performance 100% RTV silicone sealant, 83ml



Lens Options / Light Transmission

F

Frosted



F

Ordering code

MODEL	LENGTH	LENS	MOUNTING <sup>1</sup>	FINISH
BXC - Basics X-Large Channel	2M - 2 meter	F - Frosted	FC - Fixed Clip	SA - Silver Anodized

1 - Extrusion comes with 4 selected clips and 2 end caps.

Installation

All mounting channels are field cuttable using miter saw with circular blade suitable for cutting aluminum.

Ordering

Extrusions are sold separately.

Led Dotting per Extrusion with BA140-IP65

different output options may slightly vary

Extrusion	Clear Lens	Half-Frosted Lens	Frosted Lens
BXC	-	-	ND



CD SD ND  
CD - Clear Dotting  
SD - Slight Dotting  
ND - No Dotting

