

Myka 45 Wet - Installation Instructions

Model MK45W-XX

Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.
2. USE ONLY WITH CLASS 2 POWER UNIT.
3. 24 VOLTS DC.
4. SUITABLE FOR DAMP LOCATIONS.
5. SURFACE MOUNT ONLY.
6. FIXTURE SHOULD BE INSTALLED BY TWO PEOPLE.




REVO.2
02262025

1 / 5



7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com



Myka 45 Wet - Installation Instructions

Model MK45W-XX

Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.
2. USE ONLY WITH CLASS 2 POWER UNIT.
3. 24 VOLTS DC.
4. SUITABLE FOR DAMP LOCATIONS.
5. SURFACE MOUNT ONLY.
6. FIXTURE SHOULD BE INSTALLED BY TWO PEOPLE.




REVO.2
02262025

2 / 5




7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com



1.1 Determine the location of where the fixture(s) will be installed. Lay the fixture(s) on the surface, and make any necessary reference marks for the concealed bracket. Make marks 4" from each end of the fixture(s) and also every 24" in between. Use the fixture profile and mounting bracket detail, for any additional details.

1.2 Lay the concealed bracket onto the reference mark points and secure using the provided hardware.



2.1 Align the mounting brackets to the marks, followed by securing each mounting bracket with 2 screws. Snap the extrusion into the mounting brackets.

2.2 To remove the extrusion from the mounting brackets, carefully insert a flat screwdriver to the bottom edge of the extrusion then pull up until the extrusion pops up.

Myka 45 Wet - Installation Instructions

Model MK45W-XX

Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.
2. USE ONLY WITH CLASS 2 POWER UNIT.
3. 24 VOLTS DC.
4. SUITABLE FOR DAMP LOCATIONS.
5. SURFACE MOUNT ONLY.
6. FIXTURE SHOULD BE INSTALLED BY TWO PEOPLE.






REV.0.2
02262025

3 / 5



7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com



Myka 45 Wet - Installation Instructions

Model MK45W-XX

Please read all instructions prior to installation and keep for future reference!

- | | |
|--|---|
| 1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN. | 4. SUITABLE FOR DAMP LOCATIONS. |
| 2. USE ONLY WITH CLASS 2 POWER UNIT. | 5. SURFACE MOUNT ONLY. |
| 3. 24 VOLTS DC. | 6. FIXTURE SHOULD BE INSTALLED BY TWO PEOPLE. |



REVO.2
02262025

4 / 5



7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com

Power Supply Wiring Diagram

Note: Prior to installation all 24VDC wires must be present near fixture. Refer to the power supply installation instructions for additional information.



Static White
Wiring Diagram PDF

Myka 45 Wet - Installation Instructions

Model MK45W-XX

Please read all instructions prior to installation and keep for future reference!

1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN.
2. USE ONLY WITH CLASS 2 POWER UNIT.
3. 24 VOLTS DC.
4. SUITABLE FOR DAMP LOCATIONS.
5. SURFACE MOUNT ONLY.
6. FIXTURE SHOULD BE INSTALLED BY TWO PEOPLE.




REV0.2
02262025

5 / 5




7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com

power supplies at the end of the run



power supplies in the middle of the run



consecutive layout, NOT RECOMMENDED

